

(12) United States Patent Jackson et al.

(54) PATIENT POSITIONING SUPPORT STRUCTURE WITH TRUNK TRANSLATOR

(71) Applicant: Roger P. Jackson, Prairie Village, KS

Inventors: Roger P. Jackson, Prairie Village, KS (US); Lawrence E. Guerra, Mission, KS (US); Trevor A. Waggoner, Kansas

City, KS (US)

Assignee: Roger P. Jackson, Prairie Village, KS (73)(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

Appl. No.: 14/862,835

(22)Filed: Sep. 23, 2015

(65)**Prior Publication Data**

> US 2016/0008201 A1 Jan. 14, 2016

Related U.S. Application Data

(63) Continuation of application No. 12/803,192, filed on Jun. 21, 2010, now Pat. No. 9,186,291, which is a continuation-in-part of application No. 12/460,702, filed on Jul. 23, 2009, now Pat. No. 8,060,960, which

(Continued)

(51) Int. Cl. A61G 13/12 (2006.01)(2006.01)A61G 13/04 (Continued)

(52) U.S. Cl. CPC A61G 13/1295 (2013.01); A61G 13/04 (2013.01); A61G 13/08 (2013.01); (Continued)

(58) Field of Classification Search CPC A61G 13/12

US 9,510,987 B2 (10) Patent No.:

(45) Date of Patent: Dec. 6, 2016

USPC 5/600, 607, 608, 610, 611, 613, 617 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

377,377 A 2/1888 Ferry 392,743 A 11/1888 Millen (Continued)

FOREIGN PATENT DOCUMENTS

2467091 Y 12/2001 EP 2226010 B1 6/2014 (Continued)

OTHER PUBLICATIONS

Australian Patent Examination Report No. 2, AU2014200274, dated Oct. 9, 2015.

(Continued)

Primary Examiner — Fredrick Conley (74) Attorney, Agent, or Firm — Polsinelli PC

ABSTRACT

A patient support structure includes a pair of independently height-adjustable supports, each connected to a patient support. The supports may be independently raised, lowered, rolled or tilted about a longitudinal axis, laterally shifted and angled upwardly or downwardly. Position sensors are provided to sense all of the foregoing movements. The sensors communicate data to a computer for coordinated adjustment and maintenance of the inboard ends of the patient supports in an approximated position during such movements. A longitudinal translator provides for compensation in the length of the structure when the supports are angled upwardly or downwardly. A patient trunk translator provides coordinated translational movement of the patient's upper body along the respective patient support in a caudad or cephalad direction as the patient supports are angled upwardly or downwardly for maintaining proper spinal biomechanics and avoiding undue spinal traction or compression.

11 Claims, 17 Drawing Sheets

